

Cuplaje rapide pentru AER - Push in fittings

Valabil din 01.11.09

Cuplaj rapid - drept

D



Denumire	Forma	Tub-Diam.Ext.	Pret Lei/buc
DPU 04	drept	4	2.13
DPU 06	drept	6	2.21
DPU 08	drept	8	2.43
DPU 10	drept	10	3.03
DPU 12	drept	12	3.43
DPU 14	drept	14	11.91
DPU 16	drept	16	11.91

Cuplaj rapid - cot 90°

D



KPV 04	90°	4	2.13
KPV 06	90°	6	2.38
KPV 08	90°	8	2.62
KPV 10	90°	10	3.03
KPV 12	90°	12	3.43
KPV 14	90°	14	11.91
KPV 16	90°	16	11.91

Cuplaj rapid - " T "

D



TPE 04	T	4	2.94
TPE 06	T	6	2.94
TPE 08	T	8	3.01
TPE 10	T	10	4.25
TPE 12	T	12	4.64
TPE 14	T	14	14.68
TPE 16	T	16	14.68

Cuplaj rapid - reductie drept

D1-D2



RPG 6-4	drept	6 - 4	2.45
RPG 8-6	drept	8 - 6	2.77
RPG 10-8	drept	10 - 8	3.26
RPG 12-10	drept	12 - 10	4.19
RPG 14-12	drept	14 - 12	13.05

Cuplaj rapid - reductie " T "

D1-D2-D1



TPEG 4-6-4	T	4 - 6 - 4	4.42
TPEG 6-8-6	T	6 - 8 - 6	4.42
TPEG 8-10-8	T	8 - 10 - 8	5.92
TPEG10-12-10	T	10 - 12 - 10	6.42



Cuplaj rapid - reductie " T "

D2-D1-D2

TPGE 8-6-8	T	8 - 6 - 8	4.42
TPGE 10-8-10	T	10 - 8 - 10	5.92
TPGE 12-10-12	T	12 - 10 - 12	6.42

Specificatii:

Presiune de lucru	0-9,9 KGF/CM2 (0-990KPa)
Presiune negativa	-750 mmHg (10 Torr)
Temperatura de lucru	0 - 60°C

Preturile nu includ TVA.